

	Standard	Result	Product	Size (mm)
		See separate table		
		2G	RCT6301	307 x 600
	ISO 24346	6,5 mm	RCT6302	307 x 600
	ISO 24340	0,55 mm	RCT6303	307 x 600
		K-Guard+ PU coating	RCT6304	307 x 600
	Commercial	12 years *	RCP6501	1220 x 179
	Residential	30 years*	RCP6503	1220 x 179
		Thread	RCP6504	1220 x 179
	ISO 23997	7480 g m <sup>-2</sup>	RCP6506	1220 x 179
	EN 16511	Multilayer modular floorcovering panels	RCP6507	1220 x 179
			RCP6508	1220 x 179
	ISO 10874 Commercial	33:-commercial heavy	RCP6509	1220 x 179
	ISO 10874 domestic	23:-Domestic heavy	RCP6510	1220 x 179
	EN13501-1	B <sub>fl</sub> -s1		
	EN 438-2	pass (grade 5)		
	EN ISO 105-B02	pass ≥6		
	EN13329 Annex E	pass 4000 cycles		
	EN424	pass (no visible damage)		
	EN ISO 23999	pass ≤0,25%		
	ISO 24336	pass (0,2 %)		
	EN ISO 10140-1:2016 and )	ΔL <sub>w</sub> = 19 dB		
	EN ISO 10140-3:2010+A1:2015 )	ΔL <sub>LIN</sub> = 11 dB		
	ISO 24343-1	Pass ≤ 0,1 mm		
	EN13329 Annex F	pass ≥1800 mm		
	ISO 4918/ EN 425	pass 25 000 cycles		
	ISO 8302	0,052 m <sup>2</sup> K/W		
		suitable for underfloor heating max 27 °C		
	EN 13893	DS		
	DIN 51130	R10		
	French VOC regulation (ISO 16000)	A+		
		None required; please install according to our installation instructions.		
		Suitable		
		Yes		

\*subject to terms see website

\*\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204  
 Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132  
 Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14  
 Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204  
 Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386  
 e: info@designflooring.com



Manufactured to ISO9001

